



B

Safety Eyewear



## Marking on frame

Identification of the manufacturer

Number of the EN standard

Field(s) of use (where applicable)

Certification mark

Symbol for resistance to high speed particles (where applicable)

Mechanical strength	
none	without mechanical strength (filters only)
S	increased strength (filters only)
F	low energy impact (45 m/s)
B	medium energy impact (120 m/s)
A	high energy impact (190 m/s)
T	tested at extreme temperatures (-5 °C and +55 °C)

Designation	Description of application areas
none	General use Non specific mechanical risks, risks due to UV and/or visible IR light
3	Liquids Liquids (droplets and splashes)
4	Coarse dust particles Dust with > 5 µm grain size
5	Gas and fine dust particles Gas, vapour, mist, smoke, and dust with < 5 µm grain size
8	Short circuit electric arc Electric arc due to short circuit in electrical equipment
9	"Molten metal and hot solids" Splashes of molten metal and penetration of hot solids

## Marking on lens

Scale numbers (filters only)

Identification of the manufacturer

Optical class

Symbol for mechanical strength

Mechanical strength	
none	without mechanical strength (filters only)
S	increased strength (filters only)
F	low energy impact (45 m/s)
B	medium energy impact (120 m/s)
A	high energy impact (190 m/s)
T	tested at extreme temperatures (-5 °C and +55 °C)

Symbol for non adherence of molten metal and resistance to penetration of hot solids (optional)

Symbol for resistance to surface damage by fine particles (optional)

Symbol for resistance to fogging (optional)

Certification mark

## Safety Spectacles



9199 265



9199 286



9199 280

### uvex x-fit

- classic safety spectacles with good coverage of the whole eye area
- lightweight at just 23 grams
- uvex supravision coating technology
- innovative hinged side arm design
- metal-free

uvex x-fit			
Art. no.	9199 265	9199 280	9199 286
Version	uvex supravision excellence	uvex supravision excellence sunglare filter	uvex supravision excellence
Standard Frame	EN 166, EN 170 blue translucent W 166 FT CE	EN 166, EN 172 grey translucent W 166 FT CE	EN 166, EN 170 grey translucent W 166 FT CE
Lens	PC clear UV 400 2C-12 W1 FTKN CE	PC grey 23% sunglare filter UV 400 5-25 W1 FTKN CE	PC amber UV 400 2C-12 W1 FTKN CE



9193 376



9193 880



9193 280

### uvex sportstyle

- featherlight safety spectacles with a sporty design
- optimum vision thanks to uvex lens geometry
- uvex supravision coating technology
- soft, adjustable nose piece and soft, non-slip ear pieces (uvex duo component technology) ensure a secure, pressure-free fit

uvex sportstyle			
Art. no.	9193 376	9193 280	9193 880
Design	uvex supravision extreme	uvex supravision extreme sunglare filter	uvex supravision variomatic self-tinting lenses
Standard Frame	EN 166, EN 170 black, petrol W 166 FT CE	EN 166, EN 172 white, black W 166 FT CE	EN 166, EN 172 black, anthracite W 166 FT CE
Lens	PC clear UV 400 2C-12 W1 FTKN CE	PC grey 23% UV 400 5-25 W1 FTKN CE	PC light green UV 400 5-11< 2 W1 FTN CE